

TECHNICAL SPECIFICATION

(from series 2021 on)



BeachTech 1500

Data sheet

Cleaning method		BeachTech 1500
		Screening technique with oscillating screen and loading paddles
Tractor requirements		
	Recommended power output	48 kW (65 hp) – 62 kW (85 hp) **
	4-wheel-drive	
	Differential lock	
	3-point-hitch cat. 1 or 2	
	PTO shaft	6 spline, 1 3/8"
	Power take-off AR NORM	540 rpm
	Power supply	12V
Dimensions		
Length	Vehicle length	5,430 mm
	Vehicle width	2,480 mm
Width	With finisher	2,800 mm
	Working width	1,600 mm
Height	Overall vehicle height	2,400 mm
	Unloading hopper max.	2,600 mm
Tires		
	Wide-base	520/50-17
Weight		
	Net weight	3,120 kg
	Technically permissible total weight	3,500 kg *
Tank capacity		
	Hydraulic oil	80 L
Performance		
	Area coverage up to	17,000 m ² /h **
Working depth		
	up to	15 cm **
Capacity		
	Collection hopper	1.50 m ³
Speed		
	Operating speed max.	12 km/h **
	Road traffic max.	25 km/h // 40 km/h *

The possibility of changes to the product after the editorial closing date for this publication cannot be ruled out.

* Road transport according to local regulation

** Depending on the soil conditions

Dealer stamp

BeachTech

Phone: +49 7392 900 - 461

Email: info@beach-tech.com

www.beach-tech.com