

# TECHNICAL SPECIFICATION

(from series 2019 on)



# BeachTech 5500

## Data Sheet

<b>Cleaning method</b>		
		Screening technique with oscillating screen and loading paddles
<b>Engine</b>		
	Type	Deutz TD 2.9 L4
	Number of cylinders	4
	Intake system	Turbocharger
	Power output	55 kW (74 hp) @ 2,400 rpm
	Capacity	2,925 cm <sup>3</sup>
	Emission standards	EU Stage V (EPA Tier 4) or EU Stage III b (EPA Tier 4)
<b>Drive</b>		
		Hydrostatic all-wheel drive with 3-tires design
<b>Dimensions</b>		
Length		5,525 mm
Width	With standard tires (wide tires)	2,450 mm
	Working width	1,600 mm
	Finisher	2,800 mm
Height	Vehicle (rotating beacon)	2,420 mm
	Unloading hopper max.	2,600 mm
Turning radius		on the spot
<b>Tires</b>		
	Wide, low pressure	500/50 x 17
<b>Weight</b>		
	Weight	4,550 kg
	Technically permissible total weight	5,600 kg *
<b>Tank capacity</b>		
	Diesel	80 l
	Hydraulic oil	75 l
<b>Sound power</b>		
at 2,600 rpm	According to ISO 4254-1:2008	Driver's seat 79 db (A)
<b>Performance</b>		
	Area coverage up to	22,000 m <sup>2</sup> / h
<b>Working depth</b>		
	up to	15 cm **
<b>Capacity</b>		
	Collection hopper	1.5 m <sup>3</sup>
<b>Speed</b>		
	Operating speed max.	15 km/h **
	Road traffic max.	15 km/h *

The possibility of changes to the product after the editorial closing date for this publication cannot be ruled out.

\* Road transport according to local regulation

\*\* Depending on the soil condition

**Dealer Stamp**

**BeachTech**

Tel.: +49 7392 900 - 461  
 Email: info@beach-tech.com  
 www.beach-tech.com